




## **BA502**

TECHNICAL	CDECIE	
TECHNICAL	SELCIE	ICH HUHA


CODE	BA502	BA502/24V
ELECTRICAL SPECIFICATIONS  POWER SUPPLY  CURRENT (A)  POWER (W)	230V 50Hz 1.4 300	24V cc 3.2 90
PERFORMANCE DATA SPEED (rpm) TORQUE(Nm) MAX. LEAF LENGTH(METERS)	1 300 2,5	1.2 300 2,5
DIMENSIONAL AND GENERAL DATA INGRESS PROTECTION (IP) OPERATING TEMP (°C MIN/MAX) DIMENSIONS (MM) WEIGHT(KG)	68 -20 +50 °C 392x157x128 15	68 -20 +50 °C 392x157x128 14

Installation reference

- [1] Blinker
- [2] Antenna
- [3] Key selector
- [4] Photocell transmitter
- [5] Control unit with radio receiver
- [6] BA502 gearmotor
- [7] BA502 gearmotor
- [8] Photocell receiver
- [9] Radiotransmitter
- [10] Second photocell receiver
- [11] Column for photocell
- [12] Second photocell transmitter
- [13] Column for photocell



## DIMENSIONS



**ACCESSORIES** 



BOX/002 galvanized steel foundation box



COVER/502 stainless steel finishing plate for BOX002/003



BOX/003 stainless steel foundation box



COVER/502 PLUS stainless steel finishing plate for BOX006



BOX/004 self- supporting foundation box



FCM Mechanical limits for BOX006



BOX/006 galvanized heavy seel foundation box



SOLAR/24 Solar charger

